CARTER-HOFFMANN

Crisp 'N Hold - Crispy Food Hot Holding Station





Features:

- Construction Welded cabinet construction with outer cabinet welded to cabinet liner. Fasteners attach top and back panels for access to heater components. Rear-mounted cord with stainless steel cord wrap.
- Cabinet Material All stainless steel construction: 20 gauge polished exterior and 20 gauge interior. High temperature polycarbonate rail on front of cabinet to minimize hot surface temperatures in serving area.
- Insulation High density fibreglass, full 1" thick continuous wrapround type in bottom and sides.
- ◆Food Bay Removable all stainless steel food grate. Embossed surface with precision engineered holes to allow even heating. Slotted to accommodate stainless steel product dividers: two dividers provided with CNH18.
- Grease Filter Removable filter traps oils. Dishwasher-safe.
- •Collection Pan Integrated bottom mounted pan collects excess oils and pulls out for cleaning.
- ◆Legs 1" (25mm) rubber feet.
- ◆Controls Electrical mechanical thermostat mounted inside electrical portion of cabinet. Factory pre-set temperature of 88°C (only accessible with tools). On/off toggle switch with rubber boot.
- Heating System Forced air heating system located in rear housing.
 Motor isolated from heated air for extended life. Electrical resistance
 900 watt heaters with forced air blowers and ducts to direct warm air.
 Heated air is discharged through circular openings in the bottom of a grate. Grate embossed with circular texture to reduce hot metal contact with food
- Performance Capable of heating to 88°C. Preheat to 88°C in approximately 10 minutes.







Taylor UK (a division of HTG Trading Ltd)

106 Claydon Business Park, Gt. Blakenham,
Ipswich, Suffolk, IP6 ONL, United Kingdom

0800 838 896 - sales@taylor-company.co.uk
www.taylor-company.co.uk

NH18 - Crisp 'N Hold - Crispy Food Hot Holding Station

CNH₁₈





Crisp 'N Hold - Crispy Food Hot Holding Static	Crisp 'N	I Hold -	Crispy	Food Hot	Holding	Statio
--	----------	----------	--------	----------	---------	--------

ITEM No.




SIDE VIEW









TOP VIEW

CNH18	SINGLE PHASE		
External dimensions (WxDxH)	446 x 737 x 451 mm		
Capacity	1050 Cu In.		
No. Sections	3		
Weight	30 Kg		
Operating temperature	88°C		
Nominal power	1745 W		
Voltage	230v / 50Hz / 1Ph		
Total amp draw	7.6 amps		
Circuit breaker/fuse	13 amp		
Power socket	13 amp (1P+N+E)		

A dedicated power supply is required for safe operation. Equipment should never be operated on any form of extension lead, please consult a qualified electrician for correct installation advice.





Taylor UK (a division of HTG Trading Ltd) 106 Claydon Business Park, Gt. Blakenham, Ipswich, Suffolk, IP6 ONL, United Kingdom 0800 838 896 - sales@taylor-company.co.uk www.taylor-company.co.uk